



FA 20 402 07EXO, FA 20 402 10EXO, FA 20 402 15EXO

P. 1 | 2

Melixon-S

EXO



FA 20 402 07EXO = FA 20 402 07 + FA 20 EXO 07

FA 20 402 10EXO = FA 20 402 10 + FA 20 EXO 10

FA 20 402 15EXO = FA 20 402 15 + FA 20 EXO 15



HS CODE
84798997
CARTON SIZE / PCS.
FA 20 402 07EXO : 48 x 28 x 32 cm / 1
FA 20 402 10EXO : 40 x 30 x 24 cm / 1
FA 20 405 15EXO : 62 x 34 x 37 cm / 1
AET N°PPE-3442-24135-Cert (FA 20 402 07)
AET N°PPE-3464-24135-Cert (FA 20 402 10)
AET N°PPE-3465-24135-Cert (FA 20 402 15)
ANCCP Certification Agency S.r.l. N°0302 Via dello Struggino, 6 57121 LIVORNO (LI) - Italy
MODULE D FI14/14003.12
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 20 402 07EXO	FA 20 402 10EXO	FA 20 402 15EXO
 LG. KG	7 m	10 m	15 m
	140 KG		
 MAT.	Polyamide 6 - 30% fiber glass		
	STEEL Ø4.8 mm		
	STEEL		
	QUARTER / DOUBLE ACTION		
R(kN)	x2		
	12 kN		
+	YES		
	Integrated exoskeleton FA 20 EXO 07	PPE-R 11.060 Integrated exoskeleton FA 20 EXO 10	Integrated exoskeleton FA 20 EXO 15
	4.58 KG	5.35 KG	8.74 KG


 LG.
KG
 Longueur Poids maxi utilisateur
 Length Max. user weight
 Longitud Peso máximo del usuario
 Lunghezza Peso Max. dell'utente
 Länge Höchstgewicht des Benutzers


 MAT.
 Matière carter / câble
 Material of casing / wire rope
 Material cárter / cable
 Material dei carter / cavo
 Material Gehäuse / Seil


 Matière connecteur haut / connecteur bas
 Material of top connector / bottom connector
 Material conector alto / conector bajo
 Materiale connettore alto / connettore basso
 Material oberes / unteres Verbindungselement


 360°
 Nombre d'émerillons
 Number of swivels
 Cantidad de eslabones giratorios
 Numero di tornichetti
 Anzahl der Wirbel


 4.50mm
 Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
 Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
 Zugelassen für Arbeiten in der Nähe scharfer Kanten