





TRION



ZONE 1



HS CODE
84798997
CARTON SIZE / PCS.
60 x 40 x 24 cm / 1
AET N°PPE-3437-24135-Cert
ANCCP Certification Agency S.r.l. N°0302 Via dello Struggino, 6 57121 LIVORNO (LI) - Italy
MODULE D FI14/14003.12
SGS Fimko Oy, N°0598 Takomotie 8, 380 HELSINKI, Finland
ACKNOWLEDGEMENT OF RECEIPT N°1120/1/2020 (ATEX)
Technická Inšpekcia, a.s. N°1354 Trnavská cesta 56, 821 01 Bratislava, Slovenská Republika

REF.	FA 20 410 30
LG. 	30 m
KG	MAX. 140 KG
CE	EN 360:2023
MAT. 	Polyamide 6 - 30% fiber glass / 
	 QUARTER / DOUBLE ACTION with fall indicator
	x1
R(kN)	12 kN
	NO
+	IEC 60529  EN 80079-36:2016, EN 80079-37:2016 – ATEX Zone 1
	20.17 KG

LG. 	MAT. 		
Longueur Poids maxi utilisateur Length Max. user weight Longitud Peso máximo del usuario Lunghezza Peso Max. dell'utente Länge Höchstgewicht des Benutzers	Matière carter / câble Material of casing / wire rope Material cárter / cable Material dei carter / Cavo Material Gehäuse / Seil	Matière connecteur haut / connecteur bas Material of top connector / bottom connector Material conector alto / conector bajo Materiale connettore alto / connettore basso Material oberes / unteres Verbindungselement	Nombre d'émerillons Number of swivels Cantidad de eslabones giratorios Numero di tornichetti Anzahl der Wirbel



Indice de protection relatif à l'étanchéité (poussière et eau)
Degree of protection related to sealing (dust and water)
Índice de protección relativo a la estanqueidad (polvo y agua)
Indice di protezione relativo all'impermeabilizzazione (polvere e acqua)
IP-Schutzart (Staub und Wasser)



Homologué pour le travail à proximité d'arêtes vives
Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten