



FA 30 00X 45

P. 1|2

CURIOSITY

FA 30 000 45



HOPÉ

FA 30 001 45



HS CODE
63079098
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
AET EU N°2777/10348-03/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.12
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 30 000 45	FA 30 001 45
LG. 	320 mm / 1500 mm	320 mm / 1500 mm

	Max. 140 KG	
CE	EN 355:2002	
MAT.	 45mm PES	
	45 mm	
	---	
	0.35 KG	0.38 KG



Largeur de l'absorbeur d'énergie
 Width of the energy absorber
 Ancho del absorbedor de energía
 Larghezza del assorbitor di energia
 Breite des Falldämpfers

LG.



Longueur Poids maxi utilisateur
 Length Max. user weight
 Longitud Peso máximo del usuario
 Lunghezza Peso Max. dell'utente
 Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas
 Material of top connector / bottom connector
 Material conector alto / conector bajo
 Materiale connettore alto / connettore basso
 Material oberes / unteres Verbindungselement



Ouverture
 Gate opening
 Apertura
 Apertura
 Öffnung



Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
 Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
 Zugelassen für Arbeiten in der Nähe scharfer Kanten