




FA 60 006 10S, FA 60 006 20S, FA 60 006 40S

P. 1 | 2



II2 G Exh IIC T6 Gb



**UV-resistant
sheath**



**Protective sleeve
x2**



HS CODE

83081000

CARTON SIZE / PCS.

FA 60 006 10S : 40 x 40 x 24 cm / 25

FA 60 006 20S : 40 x 40 x 24 cm / 20

FA 60 006 40S : 40 x 40 x 24 cm / 10

AET (UE) N°2777/10792-04/E01-01

Satra Technology Europe Ltd., N° 2777,
Bracetown Business Park, Clonee,
Dublin, D15YN2P, Ireland

MODULE D FI14/14003.01

SGS Fimko Oy, N°0598
Takomotie 8,
00380 HELSINKI, Finland

REF.	FA 60 006 10S FA 60 006 20S FA 60 006 40S		
CE	EN 795:2012 Type B EN 354:2010		
	x1		
LG.	1.0 m	2.0 m	4.0 m
MAT.	PVC /  INOX Ø 8.0 mm		
R (kN) / MBS (kN)	12 kN / 25 kN		
+	UV-resistant PVC sheath, EN ISO 80079-36:2016 + EN ISO 80079-37:2016 (ATEX Zone 1)		
	0.46 kg	0.74 kg	1.40 kg



Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Quantità di utilizzatori
Anzahl der Benutzer

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture
Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)