






FA 60 008 04



FA 60 008 03

HS CODE
84283920
CARTON SIZE / PCS.
60 x 40 x 24 cm / 2
AET (UE) N°2777/10796-03/E02-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
ACKNOWLEDGEMENT OF RECEIPT N°3266/1/2020 (ATEX)
Technická Inšpekcia, a.s. N°1354 Trnavská cesta 56, 821 01 Bratislava, Slovenská Republika

REF.	FA 60 008 03	FA 60 008 04
CE	EN 795:2012 Type B	
	x1	
MAT.	ALU / STEEL / INOX	ALU / INOX
R (kN) / MBS (kN)	12 kN / 23 kN	
	80 mm → 300 mm	80 mm → 250 mm
+	 ATEX ZONE 1 EN 80079-36:2016 EN 80079-37:2016	MAX. DIELECTRIC RESISTANCE = 30 kV
	3.90 KG	3.70 KG




Nombre d'utilisateurs
 Number of users
Cantidad de usuarios
 Quantità di utilizzatori
 Anzahl der Benutzer



Protection diélectrique
 Dielectric protection
Protección dieléctrica
 Prodotto con protezione dielettrica
 Dielektrischer Schutz

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture
 Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
 Resistenza statica (in kN) / Resistenza alla rottura (in kN)
 Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)



Fixations à utiliser / Dimensions de la structure d'accueil
 Fasteners to use / Dimensions of the receiving structure
Fijaciones que deben usarse / Dimensiones de la estructura receptora
 Elementi di fissaggio da utilizzare / Dimensioni della struttura ospitante
 Zu verwendende Befestigungen / Abmessungen der Aufnahmestruktur