



FA 60 027 10



FA 60 027 12



HS CODE
73269098
CARTON SIZE / PCS.
40 x 30 x 24 cm / 100
FA 60 027 10
Certificate Of Conformity N°RQC2026-117/A2
FA 60 027 12
Certificate Of Conformity N°RQC2026-117/A1
QUINTIN CERTIFICATIONS
825 route de Romans
38160 SAINT ANTOINE L'ABBAYE, FRANCE
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598
Takomotie 8,
00380 HELSINKI, Finland


REF.	FA 60 027 10	FA 60 027 12
CE	EN 795:2012 Type A	
	x1	
MAT.		
R (kN) / MBS (kN)	12 kN / 23 kN	
	M10 ---	M12 ---
	0.06 KG	0.06 KG



R (kN) / MBS (kN)

Nombre d'utilisateurs
 Number of users
Cantidad de usuarios
 Quantità di utilizzatori
Anzahl der Benutzer

Résistance statique (en kN) / Résistance à la rupture
 Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
 Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)



Fixations à utiliser / Dimensions de la structure d'accueil
 Fasteners to use / Dimensions of the receiving structure
Fijaciones que deben usarse / Dimensiones de la estructura receptora
 Elementi di fissaggio da utilizzare / Dimensioni della struttura ospitante
Zu verwendende Befestigungen / Abmessungen der Aufnahmestruktur