










HS CODE
63079098
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
AET N°2777/10363-03/E03-01
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16025-01/E01-01
<b>Satra Technology Centre, N°0321</b> Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
<b>SGS United Kingdom Ltd., N°0120</b> Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 30 305 10   FA 30 305 15   FA 30 305 20
LG.  KG	1.0 m   1.5 m   2.0 m ----- Max. 100 KG
CE	EN 355:2002
MAT.	 45mm ARAMID
	45 mm
	 FA 50 202 17 / FA 50 207 55
	NO
+	ISO 9150:1988, ISO 15025:2002
	1.10 KG   1.15 KG   1.19 KG



**Largeur de l'absorbeur d'énergie**  
 Width of the energy absorber  
**Ancho del absorbedor de energía**  
 Larghezza del assorbitore di energia  
**Breite des Falldämpfers**



**Longueur Poids maxi utilisateur**  
 Length Max. user weight  
**Longitud Peso máximo del usuario**  
 Lunghezza Peso Max. dell'utente  
 Länge Höchstgewicht des Benutzers



**Sangle pouvant résister jusqu'à des températures maximales de 371°C**  
 Strap that can withstand temperatures up to 371 °C  
**Correa que puede resistir temperaturas máximas de hasta 371 °C**  
 Cinghie possono resistere alle temperature di massimo 371°C  
 Gurt hitzeresistent bis maximal 371°C



**Matière connecteur haut / connecteur bas**  
 Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
 Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**



**Ouverture**  
 Gate opening  
**Apertura**  
 Apertura  
**Öffnung**



**Homologué pour le travail à proximité d'arêtes vives**  
 Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
 Omologato per lavoro in prossimità di spigoli vivi  
 Zugelassen für Arbeiten in der Nähe scharfer Kanten



**Sangle pouvant résister à des projections de métal en fusion**  
 Strap that can withstand splashes of molten metal  
**Correa que puede resistir proyecciones de metal en fusión**  
 Cinghie possono resistere alle proiezioni di metallo in fusione  
 Gurt beständig gegen Spritzer von Schmelzmetall