










HS CODE
63079098
CARTON SIZE / PCS.
80 x 40 x 24 cm / 10
AET (EU) N°2777/10960-04/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 30 822 15
LG. (MIN./MAX.) 	1.2 m / 1.5 m (connectors included) <hr/> 140 KG
CE	EN 355:2002
MAT.	 30 mm  PES
	45 mm
	 QUARTER/ DOUBLE ACTION
	YES
+	PPE-R 11.063
	 X2 1.87 KG



Largeur de l'absorbeur d'énergie
 Width of the energy absorber
Ancho del absorbedor de energía
 Larghezza del assorbitore di energia
Breite des Falldämpfers
 LG.



Longueur Poids maxi utilisateur
 Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas
 Material of top connector / bottom connector
Material conector alto / conector bajo
 Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten