



FA 60 039 12W/12WS

FA 60 039 24W/24WS

P. 1|2



T-LINE SAFETY SYSTEM




FALL ARREST

3-IN-1

ANCHOR LINE



+
RESCUE SYSTEM

INCLUDED




2X FA 60 039 01

12 m



24 m



HS CODE

84798997

CARTON SIZE / PCS.

49,5 x 33 x 50 cm / 1

AET (UE) N° 2927/1917/160/05/25/0026


Quintin certifications, N°2927

825 route de Romans – 38160 Saint Antoine l'Abbaye
– France

MODULE D FI14/14003.01

SGS Fimko Oy, N°0598

Takomotie 8,
00380 HELSINKI, Finland

REF.	FA 60 039 12W FA 60 039 12WS		FA 60 039 24W FA 60 039 24WS	
CE	PPE Regulation (EU) 2016/425 using relevant § of EN 360 & EN 795			
	x1		x1	
MAT. 	PA /  Ø 4.5 mm	PA /  Ø 4.5 mm	PA /  Ø 4.5 mm	PA /  Ø 4.5 mm
R (kN) / MBS (kN)	12 kN / 17 kN		12 kN / 17 kN	
MAT. 				
DIM.				
ARREST DISTANCE	Mini : 1.90 m – Maxi : 4.10 m			
+	Reduced arrest distance Horizontal & vertical movement Integrated rescue system		Reduced arrest distance Horizontal & vertical movement Integrated rescue system	
	20.10 KG		21.50 KG	



Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Quantità di utilizzatori
Anzahl der Benutzer



MAT.
Matière carter / câble
Material of casing / wire rope
Material cárter / cable
Material dei carter / cavo
Material Gehäuse / Seil



MAT.
Matière connecteur haut / connecteur bas
Material of top connector / bottom connector
Material conector alto / conector bajo
Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture (en kN)
Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)

ARREST DISTANCE

Distance d'arrêt
Arrest distance
Distancia de parada
Distanza d'arresto
Anhalteabstand