



<b>HS CODE</b>
73269098
<b>CARTON SIZE / PCS.</b>
40 x 30 x 15 cm / 20
Test report 151016 (against EN795:2012 Type C) Test report 1510107 (against TS 16415:2013 Type C)
<b>DolomitiCert Scarl N°2008</b> Zona Industriale Villanova 32013 LONGARONE (BL) - Italy
<b>Technical report SPC0224619/1418/2</b> (against EN 795:2012 Type B)
<b>Satra Technology Centre Ltd</b> Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD - United Kingdom

REF.	FA 60 206 00
CE	EN 795:2012 Type B
	x1
MAT.	 INOX 316
R (kN) / MBS (kN)	12 kN / 23 kN
+	DOUBLE ACTION OPENING
	0.64 KG



**Nombre d'utilisateurs**  
Number of users  
**Cantidad de usuarios**  
Quantità di utilizzatori  
**Anzahl der Benutzer**

**R (kN) / MBS (kN)**

**Résistance statique (en kN) / Résistance à la rupture**  
Static strength / Minimum Breaking Strength  
**Resistencia estática (en kN) / Resistencia a la ruptura (en kN)**  
Resistenza statica (in kN) / Resistenza alla rottura (in kN)  
**Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)**

**DOUBLE ACTION OPENING**

**Ouverture à double action**  
Double action opening  
**Apertura de doble acción**  
Apertura a doppia azione  
**Double-Action Öffnung**