






 II2 G Exh IIC T6 Gb

HS CODE
63079098
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
AET N°2777/10962-03/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16021-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom
ACKNOWLEDGEMENT OF RECEIPT N°11ATEX6276X
Sira Certification Service Unit 6 Hawarden Industrial Park, Hawarden, CH5 3US, UK

REF.	FA 30 403 15
 LG. KG	1.5 m (connectors included) <hr/> Max. 100 KG
CE	EN 355:2002
MAT.	 45 mm PES
	45 mm  FA 50 103 22 / FA 50 208 60
 +	NO  II 2G Ex h IIC T6 Gb, EN 1149-1, ISO 80079-36, ISO 80079-37, PPE-R 11.063
	1.49 kg



Largeur de l'absorbeur d'énergie

Width of the energy absorber

Ancho del absorbedor de energía

Larghezza del assorbitore di energia

Breite des Falldämpfers

LG.



Longueur Poids maxi utilisateur

Length Max. user weight

Longitud Peso máximo del usuario

Lunghezza Peso Max. dell'utente

Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas

Material of top connector / bottom connector

Material conector alto / conector bajo

Materiale connettore alto / connettore basso

Material oberes / unteres Verbindungselement

+

Point fort

Key feature

Ventaja principal

Punti forti

Produktvorteil



Homologué pour le travail à proximité d'arêtes vives

Approved for work near sharp edges

Homologado para trabajo cerca de aristas vivas

Omologato per lavoro in prossimità di spigoli vivi

Zugelassen für Arbeiten in der Nähe scharfer Kanten