



● Sternal ● Dorsal ● Lateral




①




②



③



HS CODE
63079098
CARTON SIZE / PCS.
60 X 40 X 24 cm / 12
AET (EU) N°2777/10362-04/E05-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 10 211 00
SIZES	TU
	MAX. 140 KG (PPE-R 11.132)
CE	EN 361:2002, EN 358:2018
Attachment	Dorsal (A), Sternal (A), Lateral
	2 / 4
MAT. 	
MAT.  45 mm	Aramid
	3 / 0 / 0
+	ISO 9150:1988, ISO 15025:2002
	2.55 KG

SIZES



Taille Poids maxi utilisateur
Size Max. user weight
Tamaño Peso máximo del usuario
Dimensione Peso massimo dell' utente
Größe Höchstgewicht des Benutzers



Nombre de boucles de réglage / boucles automatiques
Number of adjustment buckles / automatic buckles
Cantidad de hebillas de ajuste / hebillas automáticas
Numero di fibbie di regolazione / fibbie autobloccanti
Anzahl der Einstellschnallen / Schnellverschluss-Schnallen

MAT. 

Matière des / boucles
Material of rings / buckles
Material de anillas en D / hebillas
Materia del D / Fibbie
Material D-Ringe/Schnallen



Nombre de dés porte-outils / poignées porte-matériel / triangles porte-accessoires
Number of tool-holding D-rings/equipment-holding handles/accessory-holding triangles
Cantidad de anillas en D portaherramientas / asas portamateriales / triángulos portaccesorios
Numero di portautensili / maniglie portamateriale / triangoli portaccessori
Anzahl der Werkzeug-D-Ringe / Werkzeug-Halteringe / Zubehör-Triangel



Sangle pouvant résister jusqu'à des températures maximales de 371°C
Strap that can withstand temperatures up to 371°C
Correa que puede resistir temperaturas máximas de hasta 371°C
Cinghie possono resistere alle temperature di massimo 371°C
Gurt hitzeresistent bis maximal 371°C



Sangle pouvant résister à des projections de métal en fusion
Strap that can withstand splashes of molten metal
Correa que puede resistir proyecciones de metal en fusión
Cinghie possono resistere alle proiezioni di metallo in fusione
Gurt beständig gegen Spritzer von Schmelzmetall