




HS CODE
83081000
Carton size / UC
60 x 40 x 48 cm / 8
<i>Test reports 160620/160952/170640/170639/180226 - Against EN 795:2012 & CEN/TS 16415:2013 Type C</i>
DolomitiCert Scarl Zona Industriale Villanova 32013 LONGARONE (ITALIE)


REF.	FA 60 217 90
CE	EN 795:2012 Type C ; TS 16415 Type C
MAT.	
DIM.	388,8 x 184,8 x 48,6 mm
	2x M12
	1.00 KG
Sys.	<input checked="" type="checkbox"/> KS 4000 <input type="checkbox"/> KS 4000 MAX-S



Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Quantità di utilizzatori
Anzahl der Benutzer

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture
Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)



Fixations à utiliser
Fasteners to use
Fijaciones que deben usarse
Elementi di fissaggio da utilizzare
Zu verwendende Befestigungen

Sys.

Système compatible
Comptible system
Sistema compatibile
Sistema compatibile
Kompatibles system