





FA 60 039 12/12S

FA 60 039 24/24S



P. 1|2

**T-LINE SAFETY SYSTEM****INCLUDED****2X FA 60 039 01**

12 m



24 m

**HS CODE**

84798997



CARTON SIZE / PCS.

49,5 x 33 x 50 cm / 1

AET (UE) N°2927/1917/160/05/25/0026

Quintin certifications, N°2927

825 route de Romans – 38160 Saint Antoine l'Abbaye
– France**MODULE D FI14/14003.01****SGS Fimko Oy, N°0598**Takomotie 8,
00380 HELSINKI, Finland


REF.	FA 60 039 12 FA 60 039 12S		FA 60 039 24 FA 60 039 24S	
CE	PPE Regulation (EU) 2016/425 using relevant § of EN 360 & EN 795			
	x1		x1	
MAT. 	PA /  Ø 4.5 mm	PA /  Ø 4.5 mm	PA /  Ø 4.5 mm	PA /  Ø 4.5 mm
R (kN) / MBS (kN)	12 kN / 17 kN		12 kN / 17 kN	
MAT. 				
DIM.	 12 m / 6 m		 24 m / 20 m / 12 m / 12 m	
ARREST DISTANCE	Mini : 1.9 m - Maxi : 3 m			
+	Reduced arrest distance Horizontal & vertical movement		Reduced arrest distance Horizontal & vertical movement	
	18.13 KG		19.53 KG	



Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Quantità di utilizzatori
Anzahl der Benutzer



MAT.
Matière carter / câble
Material of casing / wire rope
Material cárter / cable
Material dei carter / cavo
Material Gehäuse / Seil



MAT.
Matière connecteur haut / connecteur bas
Material of top connector / bottom connector
Material conector alto / conector bajo
Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement

R (kN) / MBS (kN)
Résistance statique (en kN) / Résistance à la rupture (en kN)
Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)

ARREST DISTANCE
Distance d'arrêt
Arrest distance
Distancia de parada
Distanza d'arresto
Anhalteabstand