

# REVOLTA

## SERIES




### Traitement / Treatment / Tratamiento / Trattamento / Behandlung



Oléofuge  
Oil-repellent  
Oleófuga  
Olio repellente  
Ölabweisende











Hydrofuge  
Water-repellent  
Hidrófuga  
Impermeabile  
Wasserabweisende



Anti-poussière  
Dust-repellent  
Antisuciedad  
Antimacchia  
Staubabweisende

HS CODE
63079098
CARTON SIZE / PCS.
60 x 40 x 24 / 12
AET N°2777/10958-02/E01-01
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16019-01/E01-01
<b>Satra Technology Centre, N°0321</b> Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
<b>SGS United Kingdom Ltd., N°0120</b> Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 30 309 20
LG.  KG	1.5 m / 2.0 m (connector included) ----- Max. 140 KG
CE	EN 355:2002
MAT.	 45 mm  PES + Treatment
	---
	
	NO
+	---
	0.99 KG



**Largeur de l'absorbeur d'énergie**  
Width of the energy absorber  
**Ancho del absorbedor de energía**  
Larghezza del assorbitore di energia  
**Breite des Falldämpfers**

LG.



**Longueur Poids maxi utilisateur**  
**Length** Max. user weight  
**Longitud** Peso máximo del usuario  
**Lunghezza** Peso Max. dell'utente  
**Länge** Höchstgewicht des Benutzers



**Matière connecteur haut / connecteur bas**  
Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**



**Ouverture**  
Gate opening  
**Apertura**  
Apertura  
**Öffnung**



**Homologué pour le travail à proximité d'arêtes vives**  
Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
Omologato per lavoro in prossimità di spigoli vivi  
**Zugelassen für Arbeiten in der Nähe scharfer Kanten**