



FA 30 000 XX

P. 1 | 2

HOPE



100
kg







CURIOSITY



140
kg



HS CODE
63079098
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
FA 30 000 35 : AET EU N°2777/10956-03/E01-01
FA 30 000 45 : AET EU N°2777/10348-03/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 30 000 35	FA 30 000 45
LG.  KG	220 mm / 1300 mm	320 mm / 1500 mm
CE	EN 355:2002	
MAT.	 : 35 mm PES	 : 45 mm PES
	35 mm	45 mm
	---	
	0.2 KG	0.35 KG



Largeur de l'absorbeur d'énergie
 Width of the energy absorber
Ancho del absorbedor de energía
 Larghezza del assorbitore di energia
Breite des Falldämpfers



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas
 Material of top connector / bottom connector
Material conector alto / conector bajo
 Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Ouverture
 Gate opening
Apertura
 Apertura
Öffnung



Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten